# Product Specifications

| | |
|---|---|
| **Web Thumbnail Title - MW** | Zephyr Mat |
| **Product Number for Web - MW** | Product Number 70017 (Fluffy); 70136 (Fluffy w/ Singed edging); 70018 (Tight); 70137 (Tight w/ Singed Edging) |
| **Product Specifications** | SURFACE<br>**Material:** Blend of polypropylene and polyester<br>**Weight**: 50 ounces/yard²<br><br>BACKING<br>**Material**: Rubber<br><br>**Installation:** Loose laid<br><br>**OverallMat Thickness**: 0.41 Inch |

Testing Details

| | |
|---|---|
| **Body Voltage BS EN 1815** | TESTED |
| **Colour fastness: water BS** | Grade 5 |
| **Colour fastness: rub BS EN** | Grade 4/5 |
| **C/ fastness: shampoo BS** | Grade 4/5 |
| **Dimensional stability** | TESTED |
| **Dimensional stability heat-** | TESTED |
| **Dimensional stability water** | TESTED |
| **Dynamic loading BS ISO** | PASS |
| **Electrical Resistance IBM /** | PASS |
| **Lisson Tretrad BS EN 1963-** | Grade 1 |
| **Light Colour fastness: BS EN** | Grade 6 |
| **LRV BS 8493:2008** | YES |
| **Methenamine tablet ASTM** | TESTED |
| **Static loading BS 4939/ISO** | PASS |
| **Made in USA** | true |
| **Adhesive Back/Disposable** | false |
| **Anti-Microbial** | false |
| **Chemical Resistant** | false |
| **Drainage/Holes** | false |
| **Eco-Friendly** | false |
| **Grease/Oil Proof** | false |
| **Grease/Oil Resistant** | false |
| **NFSI Certified** | false |
| **Wet Area Safe** | false |