Product Specifications

Web Thumbnail Title - MW	PharmaEze Tile
Product Number for Web -	Product Number 70002

Product Specifications

SURFACE

Material: Recycled rubber; 20% EPDM beige flecks

Backing: Recycled foam rubber

Installation: Loose laid

OVERALL TILE THICKNESS: 0.59"

Testing Details

Body Voltage BS EN 1815	TESTED
Colour fastness: water BS	Grade 5
Colour fastness: rub BS EN	Grade 4/5
C/ fastness: shampoo BS	Grade 4/5
Chemical Resistance - ASTM	No change in surface
Dimensional stability	TESTED
Dimensional stability heat-	TESTED
Dimensional stability water	TESTED
Dynamic loading BS ISO	PASS
Electrical Resistance IBM /	PASS
Elongation ASTM D412, DIE	2.16 Mpa
Flexibility - ASTM F137	Pass
Lisson Tretrad BS EN 1963-	Grade 1
Light Colour fastness: BS EN	Grade 6
LRV BS 8493:2008	YES
Methenamine tablet ASTM	TESTED
Polish Coated Floors SCOF -	Dry condition: 0.5-0.95
Resilient Floor Coverings -	0.012 in.
Static loading BS 4939/ISO	PASS
Tensile ASTM D412, DIE C	2.16 MPa
Made in USA	false
Adhesive Back/Disposable	false
Anti-Microbial	false
Chemical Resistant	true
Drainage/Holes	false
Eco-Friendly	true
Grease/Oil Proof	false
Grease/Oil Resistant	false
NFSI Certified	false
Wet Area Safe	false