Silica Sand

Quartz-based silicon dioxide granules

Filter sand is an extremely effective filter media because of its ability to hold back precipitates containing impurities. Filter sand size, angularity and hardness are the important filter sand characteristics to ensure proper filtering.

APPLICATIONS

- Filtration

PHYSICAL PROPERTIES

Shipping Weight	104 - 106 lbs/cu.ft. (1666 - 1698 g/L)	Color	Light brown to light red
Specific Gravity	2.67	Hardness	7

SUGGESTED OPERATING CONDITIONS

Flow Rate	
Working Service	Depends on fluid viscosity. Contact ResinTech

ResinTech® Inc.
INNOVATIONS IN ION EXCHANGE

CORPORATE HEADQUARTERS 1801 Federal Street Camden, NJ 08105 USA PHONE 856.768.9600 EMAIL info@resintech.com WEB resintech.com

SAFETY DATA SHEETS (SDS)

Safety Data Sheets (SDS) are available for all products on the ResinTech website. They contain important health and safety information that may be needed to protect your employees and customers from any known health and safety hazards associated with our products. We recommend that you secure and study the pertinent MSDS for our products and any other products being used.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith.
However we do not make any guarantee or warranty. We caution against using these products in an unsafe manner or in violation of any patents; further we assume no liability for the consequences of any such actions.

CORPORATE HEADQUARTERS 1801 Federal Street Camden, NJ 08105 USA PHONE 856.768.9600 EMAIL info@resintech.com WEB resintech.com