SIR-110-MP-HP

Grade: High Purity

PFAS & perchlorate selective, strong base anion resin, styrene/DVB macroporous, high purity, buffered chloride form

ResinTech SIR-110-MP-HP is a buffered chloride form PFAS, perchlorate, and nitrate selective macroporous strong base anion resin. Its unique functionality greatly increases the selectivity for nitrate while greatly decreasing the interference from sulfate ions. SIR-110-MP-HP is recommended for the removal of perchlorate, nitrate, and some perfluorinated (PFAS) compounds. Its 'HP' designation indicated it has been Gold Seal certified by the WQA for use with drinking water applications. The buffered chloride form mitigates the pH drop at startup.

FEATURES & BENEFITS

- Buffered Chloride form for pH Control
- Highest Operating Capacity
- Low Sulfate Selectivity
- Superior Physical Stability
- Controlled Particle Size

APPLICATIONS

- Drinking Water Purification
- Cartridge Applications
- Iodide Removal
- Nitrate Removal
- Perchlorate Removal
- PFAS Removal

PHYSICAL PROPERTIES

Polymer Matrix	Styrene/DVB
Polymer Type	Macroporous
Ionic Form (as shipped)	Buffered Chloride (Cl^-)
Functional Group	Tributylamine
Physical Form	Spherical Beads
Uniformity Coefficient	1.60
Particle Size	20-50 US mesh (297-841µm)
< 50 mesh (300 µm) %	< 1%
Minimum Sphericity (%)	95
Reversible Swelling	$Cl \rightarrow No_3$ -5 to -10%
Capacity (meq/mL)	0.60
Moisture Retention (%)	45 to 65
Shipping Weight	40 - 42 lbs/cu.ft. (641 - 673 g/L)
Color	White to Tan
Regenerable	Regenerable

SUGGESTED OPERATING CONDITIONS

Minimum Bed Depth	24 in. (61.0 cm)
Maximum Pressure Loss	20 psi (138 kPa)
Operating pH Range	4.0 to 10.0
Flow Rate	
Working Service	1-3 gpm/cu.ft. (8-24 BV/h)

RESINTECH INC.
INNOVATIONS IN ION EXCHANGE

CORPORATE HEADQUARTERS 1801 Federal Street Camden, NJ 08105 USA PHONE 856.768.9600 EMAIL info@resintech.com WEB resintech.com

REGENERATION DETAILS

Salt Cycle (NaCl)	10 to 15%	Displacement Flow Rate	Same as dilution water
Regenerant Level	3-10 lbs/cu.ft. (48.1-160.2 g/L)	Displacement Volume	10-15 gals/cu.ft. (1-2 BV)
Regenerant Flow Rate	0.25-1.0 gpm/cu.ft. (2-8 BV/h)	Rinse Flow Rate	Same as service flow
Regenerant Contact Time	> 30 minutes	Rinse Volume	35-60 gals/cu.ft. (5-8 BV)

***Note:** NaCl Regeneration applicable for Nitrate Removal applications only. Media is not regenerable when used to remove Perchlorate and PFAS.

PRESSURE LOSS



The graph above shows the expected pressure loss of ResinTech SIR-110-MP-HP per foot of bed depth as a function of flow rate at various temperatures.

BACKWASH EXPANSION



The graph above shows the expansion characteristics of ResinTech SIR-110-MP-HP as a function of flow rate at various temperatures.

CAPACITY



Capacity and leakage data are based on the following: 2:1 Ca:Mg ratio, 500 ppm TDS as CaCO3, 0.2% hardness in the salt and 10% brine concentration applied co-currently through the resin over 30 minutes. No engineering downgrade has been applied.

PERCHLORATE REMOVAL

ResinTech **SIR-110-MP-HP** is ideal for single use PFAS and/or perchlorate removal applications and is a cost effective method to remove trace levels of these contaminants from water. These compounds are very strongly attracted to the ResinTech **SIR-110-MP-HP**, so much so that regeneration is impractical or impossible. However, in most cases the ions can load to almost the full capacity of the resin, resulting in very long life and eliminating the need to regenerate and re-use the spent resin.

RESINTECH® INC.
INNOVATIONS IN ION EXCHANGE

CORPORATE HEADQUARTERS 1801 Federal Street Camden, NJ 08105 USA PHONE 856.768.9600 EMAIL info@resintech.com WEB resintech.com

NITRATE REMOVAL

ResinTech **SIR-110-MP-HP** can be used in the buffered chloride form to remove nitrates as well as perchlorate from potable water. **SIR-110-MP-HP** works exceptionally well in high TDS water. When treating waters with high hardness the brine dilution and displacement waters should be softened and a low hardness salt used to prevent scaling due to calcium sulfate formation during regeneration.

IODIDE REMOVAL

ResinTech **SIR-110-MP-HP**has much higher selectivity for iodide than other strong base anion resins (about 7 to 10 times higher). This high selectivity allows for single use removal of iodide against rather high concentrations of other ions with reasonable throughput capacity. Regeneration, although possible, is complicated, and cannot be accomplished with salt or other common regenerants.

CERTIFICATIONS

Meets NSF/ANSI/CAN 61

PACKAGING

Standard

1 cu.ft. Bag | 7 cu.ft. Drum
200L Drum | 25L Bag

Metric

42 cu.ft. Supersack | 5 cu.ft. Drum
1000L Supersack | 140L Drum

Shipping Weight

40 - 42 lbs/cu.ft. (641 - 673 g/L)

MATERIAL SAFETY DATA SHEETS (MSDS)

Material Safety Data Sheets (MSDS) are available for all products on the ResinTech website. They contain important health and safety information that may be needed to protect your employees and customers from any known health and safety hazards associated with our products. We recommend that you secure and study the pertinent MSDS for our products and any other products being used.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith. However we do not make any guarantee or warranty. We caution against using these products in an unsafe manner or in violation of any patents; further we assume no liability for the consequences of any such actions.

Safety Data Sheets (SDS) are available at resintech.com

RESIN TECH® INC.
INNOVATIONS IN ION EXCHANGE

CORPORATE HEADQUARTERS 1801 Federal Street Camden, NJ 08105 USA PHONE 856.768.9600 EMAIL info@resintech.com WEB resintech.com