DEQSTER Dual Charger 140W

60-DC140

Overview

The DEQSTER 140W GaN Charger 2C uses 3rd generation GaN technology, integrated overvoltage protection and DEQSTER Intelligent Power Distribution. Thanks to its Over-Temperature protection, it is a particularly safe and powerful USB-C charger with
two ports for the reliable power supply of compatible devices. With a total output of up to 140 W, it is ideal for use in educational
settings and on the go. Thanks to the two USB-C ports, two devices can be charged at the same time. Support for various output
profiles and PPS ensures flexible charging performance. The robust housing made of flame-retardant PC material provides additional
safety in everyday use.

Highlights

• 140 W total output: Powerful charging for demanding USB-C devices in the office, educational settings and on the go.
• Over-Temperature Protection
• Integrated overvoltage protection
• 3rd generation GaN technology
• DEQSTER Intelligent Power Distribution
• Two USB-C ports: Enables simultaneous charging of two devices with a power split of up to 100 W + 40 W.
• Advanced charging profiles: Supports USB-C output profiles from 5 V to 28 V as well as PPS for flexible, high-performance charging.
• Robust housing: Made from flame-retardant PC material and designed to withstand drops of up to 1 m.

Compatibility

Compatible devices	All devices with USB-C port

Key Specs

Color	White
Materials	PC
Dimension in mm	36 mm x 75 mm x 113 mm
Item weight net	248,5 g
Functions	Charge
Certifications	CE, RoHS, FCC, UK CA, GS-certified
Output Specifications	Input: 200–240 V~ / 50–60 Hz / 2 A Output USB- C1/C2: 5 V/3 A, 9 V/3 A, 12 V/3 A, 15 V/3 A, 20 V/5 A, 28 V/5 A (max. 140 W) Power Output per Port: USB-C1: 100W, USB-C2: 40W
Packaging type	Retail
Country of origin	China
Manufacturer Warranty	24 Months
Packaging Components	1x DEQSTER 140W Charger

SKU	Product name	Power Plug
60-3210	DEQSTER 140W Charger EU	

DEQSTER GmbH | Friesenweg 5H | 22763 Hamburg | +49 40 734 486 1900 |
sales@deqster.de | www.deqster.de | Technische Änderungen und Irrtümer vorbehalten.
Produktabbildungen können abweichen. Stand 01.2026

DEQSTER

DEQSTER

DEQSTER

DEQSTER