水 務 署
Water Supplies Department

香港灣仔告士打道七號入境事務大樓
Immigration Tower, 7 Gloucester Road, Hong Kong.

電子郵遞 *e-mail* wsdinfo@wsd.gov.hk

電 話 *Telephone*

圖文傳真 *Facsimile* 2824 0578

檔 號 *Reference* (2) in WSD 3321/2026 T/J(69/2026)

13 May 2026

Approval of "FLUIDMASTER" Float Operated Valve
(General Acceptance No. ZC20260304F)

Your E-Application [file-id: ETJ-GA-20260113-29] dated 19 January 2026 and subsequent submissions received by this department up to 17 April 2026 refer.

Having considered the test report ref. J30927r2 issued on 16 April 2026 by Nutek Systems (HK) Limited, this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:	Fluidmaster Water Technology
Country of Origin:	Mexico
Brand:	Fluidmaster
Details of Fitting:	3/8" Plastic float operated valve
Model:	400EP
Body Markings:	Fluidmaster®
Expiry Date:	12 May 2031

東江水供港
香港環境卓越大獎 Hong Kong Awards for Environmental Excellence
15 years+ 同心展關懷 caringorganisation

Proviso: As the fitting has not been tested for use in contact with water intended for human consumption, the fitting can only be used in flushing water plumbing systems.

This Authority hereby permits the use of the above fitting in flushing water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"The flushing volume of the flushing valve should be adjusted to suit the design of the toilet bowl so that wastes can be cleared effectively by a single flush."

"The fitting should be used within the range of working pressures specified by the manufacturer." AND

"The installed fitting should not result in backflow of water that will contaminate the flushing water supply."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in flushing water plumbing systems.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr Albert CHOW at tel. no. 3583 4086.

Yours faithfully,

(CHAN Kwok Leung, Douglas)
for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue
ME/MC] - with soft copy only

水 務 署
Water Supplies Department

香港灣仔告士打道七號入境事務大樓
Immigration Tower, 7 Gloucester Road, Hong Kong.

電子郵遞 *e-mail* wsdinfo@wsd.gov.hk

電 話 *Telephone*

圖文傳真 *Facsimile* 2824 0578

檔 號 *Reference* (2) in WSD 3321/2026 T/J(69/2026)

13 May 2026

Approval of "FLUIDMASTER" Float Operated Valve
(General Acceptance No. ZC20260304F)

Your E-Application [file-id: ETJ-GA-20260113-29] dated 19 January 2026 and subsequent submissions received by this department up to 17 April 2026 refer.

Having considered the test report ref. J30927r2 issued on 16 April 2026 by Nutek Systems (HK) Limited, this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:	Fluidmaster Water Technology
Country of Origin:	Mexico
Brand:	Fluidmaster
Details of Fitting:	3/8" Plastic float operated valve
Model:	400EP
Body Markings:	Fluidmaster®
Expiry Date:	12 May 2031

東江水供港
香港環境卓越大獎 Hong Kong Awards for Environmental Excellence
15 years+ 同心展關懷 caringorganisation

Proviso: As the fitting has not been tested for use in contact with water intended for human consumption, the fitting can only be used in flushing water plumbing systems.

This Authority hereby permits the use of the above fitting in flushing water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"The flushing volume of the flushing valve should be adjusted to suit the design of the toilet bowl so that wastes can be cleared effectively by a single flush."

"The fitting should be used within the range of working pressures specified by the manufacturer." AND

"The installed fitting should not result in backflow of water that will contaminate the flushing water supply."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in flushing water plumbing systems.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr Albert CHOW at tel. no. 3583 4086.

Yours faithfully,

(CHAN Kwok Leung, Douglas)
for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue
ME/MC] - with soft copy only