Maintenance of ULTRA LOCK PRO PVC Tiles

General Advice

-Cleaning the floor regularly is more effective, more hygienic, and less expensive than occasional intensive cleaning sessions.
-Always follow the manufacturers' recommendations and dosage instructions.
-Remove grease and oil stains immediately, as they may damage the floor surface.
-Flexible floors may be damaged by solvents.
-Rubber wheels and furniture feet may discolor the floor. Felt pads are not recommended for commercial use.
-Preferably use hard plastic feet and caps (PVC, Polyethylene).
-Light colors require more frequent cleaning.

Type of Cleaning	Equipment Used		Cleaning Products
Initial cleaning, deep cleaning, restoration, mechanical cleaning	Damp mopping Scrubber dryer or single-disc machine + red pad (or blue pad* for heavily soiled floors) ** use with caution to avoid scratching the floor*		Diluted alkaline detergent
Daily mechanical maintenance	Damp mopping Scrubber dryer or single-disc machine + red pad		Diluted neutral detergent

Protocol to be adapted according to traffic and use of the treated area

Some Tips

-Adjust dilution according to the level of dirt and water hardness.
-Do not use soap-based or overly foaming detergents.
-Do not soak the floor to avoid water infiltration between tile joints.
-Never strip the floor using abrasive pads (brown and black pads must not be used).
-Do not use any product containing acetone.
-The maximum cleaning surface must not exceed 1000 m^2 per pad (i.e. 500 m^2 per side).
-Never leave equipment with rubber caps, feet, or wheels in permanent contact with the floor (risk of migration).
-90% of dirt can be avoided by using an appropriately sized and high-quality entrance mat.

Stain Removal

-Preferably perform stain removal as soon as the stain appears to avoid penetration into the floor. Work from the outside of the stain inward.
-If necessary, use a red pad with alkaline detergent (do not use solvents or abrasive pads). Rinse with clean water.

Glue or paint:
Use cleaning naphtha or white spirit and rinse thoroughly.

Rust:
Apply a rust remover, then rinse thoroughly.

Grease, tar, ink:
Treat quickly with white spirit or an equivalent product and rinse thoroughly.

Rubber (cart wheels, trolleys, shoes):
Leave the alkaline detergent to act for 5 minutes, scrub, and rinse.

ONEFLOR-EUROPE BV
Wittestraat 10 – B-8501 HEULE
Tel.: +32 56 41 06 94
Email : info@oneflor-europe.com